



Count on it.

TimeCutter® MX3400, Model No. 75730TA



TECHNICAL SPECIFICATIONS AND FEATURES

Engine	Kawasaki FR600V-_S04-R, 13.4 kW (18.0 hp) (as per J1995), 603 cc, overhead valve, V-twin, single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. High idle speed set at 3,300 +/-100 rpm. Standard Kawasaki style paper air cleaner fitted.
Construction	Riveted and bolted 10 gauge steel.
Deck Size	86.4 cm (34.0 inch).
Deck Configuration	Right side discharge, two blade cantered mid-mounted rotary. Fabricated 10 gauge steel deck with welded reinforcements, mounting brackets and gauge wheel brackets. Frame supported. Left and right front mounted anti-scalp rollers with four height positions.
Deck Spindles	Die cast aluminum spindle housing (2). Permanently lubricated sealed precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
Height of Cut	3.8 cm to 11.4 cm (1.5 to 4.5 inches) HOC in 7 increments.
Hydro Drive Unit	Dual Hydro-gear ZT-2100 hydrostatic transaxles, belt drive with self-tensioning system.
Ground Speed	Mow: 0 to 11.3 km/h (0 to 7.0 mph). Trim: 0 to 8.9 km/h (0 to 5.5 mph). Tow: 0 to 6.4 km/h (0 to 4.0 mph). Reverse: 0 to 4.4 km/h (0 to 3.5 mph).
Wheel Base	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
Steering Control	Ergonomic, adjustable steering levers with heavy-duty dampeners.
Width	Deflector Down: 114.3 cm (45.0 inches). Deflector Up: 104.1 cm (41.0 inches).
Overall Length	190.5 cm (75.0 inches)
Overall Height	97.0 cm (38.2 inches).
Tyres	Front - 11 x 4.0-5.0, 2 ply, smooth tread, pneumatic. Rear - 18 x 6.0-8, 2 ply, super turf tread, pneumatic.
Fuel Tank Capacity	11.4 litres (single tank).
Net Weight	242.2 kg (534.0 lbs.).
Seat	40.67 cm (16.0 inch) handcrafted contoured seat, adjustable, hinged mounting, with spring suspension.
Warranty	Residential: Machine 3 years, Engine & Transaxles 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). Commercial: Machine & Transaxles 30 days, Engine 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 30 days. Attachments: 1 year. NOTE: Engine warranty is through Kawasaki USA, but administered by Toro Australia. <i>For all other conditions, refer to The Toro Warranty statement accompanying the machine.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

For additional technical and servicing information regarding this mower, refer to Service Bulletin TCSB01-21, issued April 9, 2021.

Issue Date: April 9, 2021

PLEASE NOTE: The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

ACCESSORIES AND ATTACHMENTS

Product	Part No.
Twin Bagger Kit - 34 inch	79417
Blowout Ring Kit	140-8369
Recycler Kit – 34 inch	140-3536
Hourmeter Kit	116-5461
ROPS Kit	79485
Slope Sensor Kit, TimeCutter	79486
Deck Maintenance Jack #	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056

Jack requires mount kit 140-2711 and cannot be used if Assist Bar Kit 140-2952 is fitted.

Product	Part No.
Deck Foot Lift Assist Kit	140-2059
Floor Mat Kit	140-2060
Seat Armrest Kit	140-2058
Seat Cover (W/O armrests)	117-0096
Assist Bar Kit	140-2052
Sunshade Kit	140-2054
Storage Cover	490-7516
Striping Kit – 34 inch	140-8374
Front Weight Kit	140-2050
Deluxe Seat Kit	140-2057

REGULAR MAINTANENCE ITEMS

Product	Part No.
Air Cleaner Element	11013-0727
Engine Oil Filter	49065-0721
Engine Fuel Filter	49019-0031
Rocker Cover Gasket (2 required)	119-5805, or 11061-7083
Spark Plugs (2 required)	NGK BPR4ES

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SJ or higher. Engine Oil SAE 10W-40 or 20W-50 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 1.5 litres With oil filter change – 1.7 litres
Transaxle Oil	SAE 20W-50 API Engine Oil
Transaxle Oil Capacity	1.6 to 1.65 litres per side

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Plastic Discharge Deflector	140-3548
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Idler Pulley	68-0030-03	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	117-7468	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	140-2736
Deck Spindle Drive Belt	140-5141	Rear Tyre	140-5129
Deck Spindle Pulley	127-0098	Ignition Key	63-8360
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Battery (Dry)	105-1692
Deck Spindle Shaft	117-7268	Throttle Cable	139-2403
Deck Spindle Bearing (2 required)	138-9770	Choke Cable	139-2402
Deck Belt Cover	144-1905		

Blades

Blade Type	Part No.
Standard – all applications (Bagging / Recycler / Mulch)	140-5134-03